



PACOAR

Install and Drive . . .

PACCOAR

نوع باتری (TYPE)	ظرفیت 20 ساعته (AH, 25°C)	جریان راه اندازی سرد (ACC, ISIRI) (at -18°C)	ماکزیمم ابعاد باتری (mm)			چانمایی قطب	نوع پایه
			ارتفاع (H)	عرض (W)	طول (L)		

DIN

Sealed Maintenance Free

L1	50	350	189	175	207	0	B1
L2	50	350	189	175	241	0	B1
	55	400	189	175	241	0	B1
	62	450	189	175	241	0	B1
	50	350	189	175	241	1	B1
	55	400	189	175	241	1	B1
	62	450	189	175	241	1	B1
L3	66	480	190	175	276	0	B1
	75	530	190	175	276	0	B1
	66	480	190	175	276	1	B1
	75	530	190	175	276	1	B1
L5	90	640	190	175	347	0	B1
	100	650	190	175	347	0	B1
	105	655	190	175	347	0	B1

JIS

Sealed Maintenance Free

B20	35	250	202	128	197	0	B0
B24	45	320	202	128	235	0	B0
D23	60	430	200	175	235	1	B2
D26	60	450	200	175	257	0	B2
	70	500	200	175	257	0	B2
	75	530	200	175	257	0	B2
	60	450	200	175	257	1	B2
	70	500	200	175	257	1	B2
	75	530	200	175	257	1	B2
D31	90	640	198	175	302	0	B2
	100	650	198	175	302	0	B2
	90	640	198	175	302	1	B2
	100	650	198	175	302	1	B2
E41	120	720	220	175	405	0	B0
	120	720	220	175	405	1	B0
B-TRUCK	150	900	210	222.5	485	2	B0
	170	1020	210	222.5	485	2	B0
	180	1080	210	222.5	485	2	B0
	200	1100	210	222.5	485	2	B0
	150	900	210	222.5	485	3	B0
	170	1020	210	222.5	485	3	B0
	180	1080	210	222.5	485	3	B0
	200	1100	210	222.5	485	3	B0
C-TRUCK	225	1150	217	275	485	2	B0
	240	1200	217	275	485	2	B0